

ABC POWDER TYPE FIRE EXTINGUISHERS

(Gas Cartridge Type)



IS:15683
CML - 2831861



Application :



Class A Fire : Ordinary Combustibles
For Use On Wood, Paper, Plastic & Cloths etc...



Class B Fire : Flammable Liquids
For Use On Petrol, Oil, Paints, Spirit, Plastics & Chemicals etc...



Class C Fire : Flammable Gas & Vapour
For Use On Liquified & Welding Gases etc...



Electrical Fire



MODEL	ESD - 4	ESD - 6	ESD - 9
Capacity	4 kg	6 kg	9 kg
Confirming IS Code	15683	15683	15683
Type of Extinguishers	Co ₂ Gas Cartridge Type		
Type of Extinguishing Media	Mono Ammonium Phosphate Base Dry Powder Confirming to IS:14609		
Expellant	90 gms Co ₂ Gas Cartridge	120 gms Co ₂ Gas Cartridge	200 gms Co ₂ Gas Cartridge
Diameter (Approx)	140 ± 10mm	150 ± 10 mm	175 ± 10mm
Height (Approx)	505 mm	520 mm	560 mm
Filled Weight (Approx)	8.0 kg	10.5 kg	14.0 kg
Empty weight (Approx)	4.0 kg	4.5 kg	5.0 kg
Average Discharge Time	15 sec.	20 sec.	32 sec.
Operating Temperature	-20°C to 55°C		
Working Pressure at 20°C	15.5bar		
Maximum Service Pressure	17.5bar		
Hydraulic Test Pressure	35.0bar		
Fire Rating	1A 13B	2A 21B	3A 34B
Approvals	BIS & CE	BIS & CE	BIS & CE