

IS:15683
CML - 2831861



CLEAN AGENT FIRE EXTINGUISHERS

(Stored Pressure)



Application :

Class A Fire : Ordinary Combustibles
For Use On Wood, Paper, Plastic & Cloths etc...



Class B Fire : Flammable Liquids
For Use On Petrol, Oil, Paints, Spirit, Plastics & Chemicals etc...



Class C Fire : Flammable Gas & Vapour
For Use On Liquefied & Welding Gases etc...



Electrical Fire



MODEL	ESCA - 2	ESCA - 4	ESCA - 6
Capacity	2 kg	4 kg	6 kg
Confirming IS Code	15683	15683	15683
Type of Extinguishers	Constant Pressure		
Type of Extinguishing Media	HFC-236fa Clean Agent		
Expellant	Pressurized with Nitrogen (N ₂) Gas		
Diameter (Approx)	108 ± 10mm	140 ± 10 mm	150 ± 10mm
Height (Approx)	420 mm	485 mm	510 mm
Filled Weight (Approx)	4.0 kg	8.5 kg	9.5 kg
Empty weight (Approx)	2.0 kg	4.5 kg	3.5 kg
Average Discharge Time	12 sec.	14 sec.	20 sec.
Operating Temperature	-20°C to 55°C		
Working Pressure at 20°C	15.5bar		
Maximum Service Pressure	17.5bar		
Hydraulic Test Pressure	35.0bar		
Fire Rating	8B	1A 13B	2A 21B
Approvals	BIS & CE	BIS & CE	BIS & CE